python

prepare

get python

python official site

settings

- Editors
  - Visual Studio Code
  - Vim
  - ~~Sublimetext~~
  - ~~pyCharm~~

```
$ python3 hello_world.py
```

variables and types

- 변수 이름은 snake_case로
- 문자열은 “This is a string”, 'This is also a string.' 모두 가능
- {string_variable}.title() → 첫 글자 대문자로
- {string_variable}.upeer()
- {string_variable}.lower()
- f-string
  - full_name = f“{first_name} {last_name}”
  - full_name = “{} {}”.format(fist_name, last_name)
- escape characters; \', \\, \n, \r, \t, \b, \f, \ooo, \xhh
- {string_variable}.rstrip() → 오른쪽 공백 삭제, .strip() → 양쪽 공백 제거, .lstrip() → 왼쪽 공백 제거
- numeric; integer, floating point number, underscored number → 15_000_000_000
- 상수는 대문자로; MAX_CONNECTIONS = 5000
- comments; #

```
message = "Hello Python"
print(message)
```

```
>>> import this
```

list

- 대괄호 []와 콤마 ,
- 이름을 복수형으로
- 인덱스는 0부터, [-1]은 끝에서부터의 인덱스

```
bicycles = ['trek', 'cannondale', 'redline', 'specialized']
print(bicycles)

print(bicycles[0])
print(bicycles[0].title())

bicycles[0] = 'mini bell'  # change value
bicycles.append('trek')  # append value
bicycles.insert(0, 'strida')  # insert value

del bicycles[0]  # delete
popped_bicycle = bicycles.pop()  # pop value (stack)
#popped_bicycle = bicycles.pop(0)  # pop value by index
bicycles.remove('redline')  # remove by value

bicycles.sort()  # sort permanently by alphabet
bicycles.sort(reverse=True) # reverse sort
print(sorted(bicycles))  # sort temporarily
bicycles.reverse()  #

len(bicycles)
```

list handling

```
magicians = ['alice', 'david', 'carolina']
for magician in magicians:
    print(magician)
for value in range(1, 5):  # 1 ~ 4
    print(value)
numbers = list(range(1, 6))  # numbers = [1, 2, 3, 4, 5]
even_numbers = list(range(2, 11, 2))  # even_numbers = [2, 4, 6, 8, 10]

squares = []
for value in range(1, 11):
    square = value ** 2
    squares.appen(square)
```

```
# squares = [value ** 2 for value in range(1,11)]
print(squares)

digits = [1, 2, 3, 4, 5, 6, 7, 8, 9, 0]
min(digits)
max(digits)
sum(digits)
```

- slice; 원래 리스트 유지
  - players[0:3] # index 0에서부터 3개까지 자름 [:3]
  - players[2:] # index 2부터 끝까지
  - players[-3:] # 끝에서 셋
- 복사
  - my_friends = your_friends[:]
  - my_friends = your_friends는 포인터 같은 역할
- tuple(immutable)
  - 대괄호 대신 소괄호 ()와 콤마 ,
  - 한 개 항목의 튜플이더라도 콤마 필요; my_t = (3,)
- Coding style; PEP(Python Enhancement Proposal) 8
  - 들여쓰기 공백 네 칸
  - 행 길이 79자
  - PEP 8 -- Style Guide for Python Code

if state

```
cars = ['audi', 'bmw', 'subaru', 'toyota']

for car in cars:
    if car == 'bmw':
        print(car.upper())
    else:
        print(car.title())
```

- == ; equals to
- != ; not equals
- <, ⇐, >, >=
- and, or
- in; 'mushrooms' in requested_toppings
- not in;
- boolean expression; True, False
- if, if-else, if-elif-else

```
if age < 4:  # GOOD
```

```
if age<4:  #bad
```

dictionary

- key-value pair
- 중괄호 {}

```
alien_0 = {'color': 'green', 'points': 5}

print(alien_0['color'])
print(alien_0['points'])

alien_0['x_position'] = 0
alien_0['y_position'] = 25

dict_0 = {}  # 빈 값으로 딕셔너리 선언

del alien_0['points']  # points key 제거

favorite_languages = {
    'jen': 'python',
    'sarah': 'c',
    'edward': 'ruby',
    'phil': 'python',
    }
point_value = alien_0.get('points', 'No point value assigned.')  # key가 없을 경우의 default 값을 지정하여 error 방지

user_0 = {
    'username': 'efermi',
    'first': 'enrico',
    'last': 'fermi',
    }

for key, value in user_0.items():
    print(f"\nKey: {key}")
    print(f"Value: {value}")
for name in favorite_languages.key():
    print(name.title())
for language in favorite_languages.values():
    print(language.title())
for language in set(favorite_languages.values()):  # set는 중복을 제거한 고유한 데이터 형식
    print(language.title())
```

- nesting

    - 딕셔너리 안에 리스트, 리스트 안에 딕셔너리, 딕셔너리 안에 딕셔너리…

user input and while loop

- 사용자 입력

```
message = input("Tell me something and I will repeat it back to you: ")
print(message)

prompt = "If you tell us who you are we can personalize the messages you
see."
prompt += "\nWhat is you first name? "

name = input(prompt)
print(f"\nHello, {name}!")
```

- 형변환; int(string)
- modulo operator %
- while loop

```
current_number = 1

while currnet_number <= 5:
    print(current_number)
    current_number += 1
```

```
message = ""

while message != 'quit':
  message = input(prompt)
  print(message)
```

- flag; bool 변수를 이용하여 while 처리
- break; 루푸 빠져 나가기
- continue; 루프의 처음으로
- 무한 루프 주의

function

```

```

```
def greet_user():  # 함수 정의
  """간단한 환영 인사를 표시합니다"""  # document string 혹은 docstring 따옴표 세개"""
로 둘러쌈
    print("Hello")
greet_user()

def describe_pet(animal_type, pet_name='dog'):  # 기본 값이 있는 파라메터는 뒤쪽에
  """반려동물에 관한 정보를 출력합니다"""
    print(f"\nI have a {animal_type}.")
    print(f"My {animal_type}'s name is {pet_name.title()}.")
    #return 값
describe_pet('hamster', 'harry)
describe_pet(animal_type='hamster', pet_name='harry')
describe_pet(pet_name='harry', animal_type='hamster')
describe_pet('willie')
```

- function에 리스트를 넘길 때 function_name(list_name[:])로 사본을 넘기면 원래 값이 유지 (Call by value), 리스트를 넘기면 원래 리스트가 수정됨 (Call by reference).
- 함수 정의/호출시 기본값 지정할 때 공백을 쓰지 않는다

```
def make_pizza(*toppings):  # 여러 개의 매개변수 빈 튜플
def build_profile(first, last, **user_info):  # 빈 딕셔너리
```

- 함수를 모듈로 저장
    - 소문자

```
import pizza  # pizza.py 파일을 열고 그 파일에 있는 모든 함수 사용

pizza.make_pizza()  # pizza 모듈 안의 make_pizza() 함수 호출

# 모듈에서 일부 함수만 사용
from module_name import function_name
from module_name import function_0, function_1, function_3

# 별칭; 함수의 별칭으로 호출
from pizza import make_pizza as mp
from module_name import function_name as fn

# 모듈의 별칭
import pizza as p
import module_name as mn

# 모든 함수 비추천
from pizza import *
from module_name import *
```

class

```
class Dog:  # 대문자로 시작
  """개를 모델화하는 시도"""  # docstring
    def __init__(self, name, age):  # 생성자 메서드, 반드시 구현
        ""name과 age 속성 초기화"""
        self.name = name
        self.age = age
    def sit(self):
   """명령에 따라 앉는 개"""
        print(f"{self.name} is now sitting.")
    def roll_over(self):
   """명령에 따라 구르는 개"""
        print(f"{self.name} rolled over!")
my_dog = Dog('Willie', 6)
my_dog.sit()
my_dog.roll_over()
```

- super() 메서드로 superclass에 접근
- override.
- CamelCase

```
from car import Car  # car.py 안에 Car 클래스 하나만 있을 경우
from car import ElectricCar  # car.py 안에 여러 클래스 중 ElectricCar 만 임포트
from car import Car, ElectricCar  # car.py 안에 Car, ElectricCar 클래스 임포트
import car  # car.py 안에 있는 모든 클래스 임포트

from module_name import *

from electric_car import ElectricCar as EC  # electric_car.py의 ElectricCar 클래스를 EC로 임포트
```

- python standard library

```
from random import randint
randint(1, 6)

from random import choice
choiced_value = choice(list_values)
```

file and exception

```
# 기본적인 읽기
file_path = '/home/..../openfile.txt'
with open(file_path) as file_object:
    contents = file_object.read()
print(contents)

# 라인씩 읽기
with open(filename) as file_object:
    for line in file_object:
        print(line)
filename = 'pi_digits.txt'
with open(filename) as file_object:
    lines = file_object.readlines()
for line in lines:
    print(line.rstrip())
print(f"{pi_string[:52]...")  # 52번째 캐릭터까지만

# write a file
filename = 'prg.txt'

with open(filename, 'w') as file_object:  # w: write mode, r: read mode, a:
append mode, r+; read and write. default is 'r'
    file_object.write("I love programming.")
#open(filename, encoding='utf-8')
```

```
try:
    print(5/0)
except ZeroDivisionError:  # FileNotFoundError,
    print("You can't divide by zero!")
    #pass  # 조용히 실패하기, except 블럭 안에 아무것도 하지 않고 pass만.
else:
    print("try block success.")
```

- string.replace(find_string, replace_string)
- string.count(find_string) returns count

```
import json

json.dump(contents, file_object)  # contents를 file_object에 저장, with
open(filename, 'w') 사용
loaded_object = json.load(file_object)  # with open(filename)
```

- refactoring; 코드를 더 사용하기 쉽게 재구성

code test

game

data visualization

web application

From:
https://theta5912.net/ - **reth**

Permanent link:
https://theta5912.net/doku.php?id=public:computer:python&rev=1627920467

Last update: **2021/08/03 01:07**