

Elements of Document



- 구조
 - 헤더, 섹션
 - 목차
 - **bold**, *italic*, underlined, monospaced, ~~deleted~~, subscript, ^{superscript}, ruby text: 文字(もじ),
 - 문장, 문단
 - 개행
 - 링크; 내부링크, 외부링크, 인터위키
 - 이미지; 링크, 화면 출력
 - 동영상; 링크, 화면 출력
 - 움직이는 이미지; gif,
 - footnote
 - 미디어 파일; audio,
 - 기타 파일; pdf, doc, rtf, xls, csv,
 - 목록; 순서 없는, 순서 있는, 접힘 목록
 - 이모지
 - 문자 변경 → ← ↔ ⇒ ⇐ ⇔ » « - — 640x480 © ™ ® “He thought 'It's a man's world'...”
 - 인용
 - 표
 - 포맷 없음
 - 코드 블록
 - syntax highlighting
 - downloadable code
 - Embedding HTML<html>

This is some inline HTML </html><HTML> <p style="border:2px dashed red;">And this is some block HTML</p> </HTML>

- Control Macros
- 구분선
- mathjax
- diagrams
- 페이지별 css 설정
- 태그
- 기능
 - 새페이지
 - 문서 템플릿
 - 검색
 - 카테고리(네이스페이스) 리스트
 - 최근 변경
 - todo
 - export; pdf, markdown, only text
 - include
 - snippets
 - history
 - backlinks
 - orphaned

- text → data
 - markdown embed
 - rss
 - ACL
 - extentions
 - theme
 - 문서 내 acl
 - 이동(rename)
 - site map
- 협업 기능????

Formatting Syntax

 [DokuWiki](#) supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages. Simply have a look at the source of this page by pressing "Edit this page". If you want to try something, just use the [playground](#) page. The simpler markup is easily accessible via  [quickbuttons](#), too.

Basic Text Formatting

DokuWiki supports **bold**, *italic*, underlined and monospaced texts. Of course you can ***combine*** all these.

```
DokuWiki supports bold, //italic//, __underlined__ and 'monospaced'
texts.
Of course you can __//'combine'//__ all these.
```

You can use _{subscript} and ^{superscript}, too.

```
You can use <sub>subscript</sub> and <sup>superscript</sup>, too.
```

You can mark something as ~~deleted~~ as well.

```
You can mark something as <del>deleted</del> as well.
```

Paragraphs are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks
Note that the two backslashes are only recognized at the end of a line
or followed by
a whitespace \\this happens without it.

```
This is some text with some linebreaks\\ Note that the
two backslashes are only recognized at the end of a line\\
or followed by\\ a whitespace \\this happens without it.
```

You should use forced newlines only if really needed.

Links

DokuWiki supports multiple ways of creating links.

External


External links are recognized automagically: <http://www.google.com> or simply www.google.com - You can set the link text as well: [This Link points to google](#). Email addresses like this one: andi@splitbrain.org are recognized, too.

```
DokuWiki supports multiple ways of creating links. External links are
recognized
automagically: http://www.google.com or simply www.google.com - You can set
link text as well: [[http://www.google.com|This Link points to google]].
Email
addresses like this one: <andi@splitbrain.org> are recognized, too.
```

Internal

Internal links are created by using square brackets. You can either just give a [pagename](#) or use an additional [link text](#).

```
Internal links are created by using square brackets. You can either just
give
a [[pagename]] or use an additional [[pagename|link text]].
```

 [Wiki pagenames](#) are converted to lowercase automatically, special characters are not allowed.

You can use [namespaces](#) by using a colon in the pagename.

```
You can use [[some:namespaces]] by using a colon in the pagename.
```

For details about namespaces see  [namespaces](#).

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to [this Section](#).

```
This links to [[syntax#internal|this Section]].
```

Notes:

- Links to [existing pages](#) are shown in a different style from [nonexisting](#) ones.
- DokuWiki does not use [CamelCase](#) to automatically create links by default, but this behavior can be enabled in the [config](#) file. Hint: If DokuWiki is a link, then it's enabled.
- When a section's heading is changed, its bookmark changes, too. So don't rely on section linking too much.

Interwiki

DokuWiki supports [Interwiki](#) links. These are quick links to other Wikis. For example this is a link to Wikipedia's page about Wikis: [Wiki](#).

```
DokuWiki supports [[doku>Interwiki]] links. These are quick links to other Wikis.  
For example this is a link to Wikipedia's page about Wikis: [[wp>Wiki]].
```

Windows Shares

Windows shares like [this](#) are recognized, too. Please note that these only make sense in a homogeneous user group like a corporate [Intranet](#).

```
Windows Shares like [[\\server\share|this]] are recognized, too.
```

Notes:

- For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer per default (and only in the “local zone”).
- For Mozilla and Firefox it can be enabled through different workaround mentioned in the [Mozilla Knowledge Base](#). However, there will still be a JavaScript warning about trying to open a Windows Share. To remove this warning (for all users), put the following line in `conf/lang/en/lang.php` (more details at [localization](#)):

```
<?php  
/**  
 * Customization of the english language file  
 * Copy only the strings that needs to be modified  
 */  
$lang['js']['nosmblinks'] = '';
```

Image Links

You can also use an image to link to another internal or external page by combining the syntax for links and [images](#) (see below) like this:

```
[[http://php.net|{{wiki:dokuwiki-128.png}}]]
```



Please note: The image formatting is the only formatting syntax accepted in link names.

The whole [image](#) and [link](#) syntax is supported (including image resizing, internal and external images and URLs and interwiki links).

Footnotes

You can add footnotes ¹⁾ by using double parentheses.

You can add footnotes ((This is a footnote)) by using double parentheses.

Sectioning

You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically - this can be disabled by including the string `~~NOTOC~~` in the document.

Headline Level 3

Headline Level 4

Headline Level 5

```
==== Headline Level 3 ====  
=== Headline Level 4 ===  
== Headline Level 5 ==
```

By using four or more dashes, you can make a horizontal line:

Media Files

You can include external and internal [images, videos and audio files](#) with curly brackets. Optionally you can specify the size of them.



Real size:



Resize to given width:



Resize to given width and height²⁾:



Resized external image:

```
Real size:                {{wiki:dokuwiki-128.png}}
Resize to given width:    {{wiki:dokuwiki-128.png?50}}
Resize to given width and height: {{wiki:dokuwiki-128.png?200x50}}
Resized external image:  {{https://secure.php.net/images/php.gif?200x50}}
```

By using left or right whitespaces you can choose the alignment.



```

{{ wiki:dokuwiki-128.png}}
{{wiki:dokuwiki-128.png }}
{{ wiki:dokuwiki-128.png }}

```

Of course, you can add a title (displayed as a tooltip by most browsers), too.



```

{{ wiki:dokuwiki-128.png |This is the caption}}

```

For linking an image to another page see [Image Links](#) above.

Supported Media Formats

DokuWiki can embed the following media formats directly.

Image	gif, jpg, png
Video	webm, ogv, mp4
Audio	ogg, mp3, wav
Flash	swf

If you specify a filename that is not a supported media format, then it will be displayed as a link instead.

By adding `?linkonly` you provide a link to the media without displaying it inline

```

{{wiki:dokuwiki-128.png?linkonly}}

```

[dokuwiki-128.png](#) This is just a link to the image.

Fallback Formats

Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you can upload your file in different formats for maximum browser compatibility.

For example consider this embedded mp4 video:

```

{{video.mp4|A funny video}}

```

When you upload a `video.webm` and `video.ogv` next to the referenced `video.mp4`, DokuWiki will automatically add them as alternatives so that one of the three files is understood by your browser.

Additionally DokuWiki supports a “poster” image which will be shown before the video has started. That image needs to have the same filename as the video and be either a jpg or png file. In the example above a video .jpg file would work.

Lists

Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by two spaces and use a * for unordered lists or a - for ordered ones.

- This is a list
 - The second item
 - You may have different levels
 - Another item
1. The same list but ordered
 2. Another item
 1. Just use indentation for deeper levels
 3. That's it

```
* This is a list
* The second item
  * You may have different levels
* Another item

- The same list but ordered
- Another item
  - Just use indentation for deeper levels
- That's it
```

Also take a look at the [FAQ on list items](#).





















Text Conversions

DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML.

The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for typography replacements, but can be configured to use other HTML as well.

Text to Image Conversions

DokuWiki converts commonly used [emoticons](#) to their graphical equivalents. Those [Smileys](#) and other images can be configured and extended. Here is an overview of Smileys included in DokuWiki:

-  8-)
-  8-O
-  :-(
-  :-)
-  =)
-  :-/
-  :-\
-  :-?
-  :-D
-  :-P
-  :-O
-  :-X
-  :-|
-  ;-)
-  ^_^
-  :?:
-  !:
-  LOL
-  **Fix Me!** FIXME
-  **Delete!** DELETEME

Text to HTML Conversions

Typography: [DokuWiki](#) can convert simple text characters to their typographically correct entities. Here is an example of recognized characters.

→ ← ↔ ⇒ ⇐ ⇔ » « – — 640×480 © ™ ® “He thought 'It's a man's world'...”

```
-> <- <-> => <=<=> >> << -- --- 640x480 (c) (tm) (r)
"He thought 'It's a man's world'..."
```

The same can be done to produce any kind of HTML, it just needs to be added to the [pattern file](#).

There are three exceptions which do not come from that pattern file: multiplication entity (640×480), 'single' and “double quotes”. They can be turned off through a [config option](#).

Quoting

Some times you want to mark some text to show it's a reply or comment. You can use the following syntax:

```
I think we should do it
> No we shouldn't
>> Well, I say we should
> Really?
>> Yes!
>>> Then lets do it!
```

I think we should do it

```
No we shouldn't
| Well, I say we should
| Really?
| Yes!
| | Then lets do it!
```

Tables

DokuWiki supports a simple syntax to create tables.

Heading 1	Heading 2	Heading 3
Row 1 Col 1	Row 1 Col 2	Row 1 Col 3

Heading 1	Heading 2	Heading 3
Row 2 Col 1	some colspan (note the double pipe)	
Row 3 Col 1	Row 3 Col 2	Row 3 Col 3

Table rows have to start and end with a | for normal rows or a ^ for headers.

```

^ Heading 1      ^ Heading 2      ^ Heading 3      ^
| Row 1 Col 1   | Row 1 Col 2   | Row 1 Col 3   |
| Row 2 Col 1   | some colspan (note the double pipe) |
| Row 3 Col 1   | Row 3 Col 2   | Row 3 Col 3   |

```

To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to have always the same amount of cell separators!

Vertical tableheaders are possible, too.

	Heading 1	Heading 2
Heading 3	Row 1 Col 2	Row 1 Col 3
Heading 4	no colspan this time	
Heading 5	Row 2 Col 2	Row 2 Col 3

As you can see, it's the cell separator before a cell which decides about the formatting:

```

|           ^ Heading 1      ^ Heading 2      ^
^ Heading 3 | Row 1 Col 2   | Row 1 Col 3   |
^ Heading 4 | no colspan this time |
^ Heading 5 | Row 2 Col 2   | Row 2 Col 3   |

```

You can have rowspans (vertically connected cells) by adding :: into the cells below the one to which they should connect.

Heading 1	Heading 2	Heading 3
Row 1 Col 1		Row 1 Col 3
Row 2 Col 1	this cell spans vertically	Row 2 Col 3
Row 3 Col 1		Row 2 Col 3

Apart from the rowspan syntax those cells should not contain anything else.

```

^ Heading 1      ^ Heading 2      ^ Heading 3      ^
| Row 1 Col 1   | this cell spans vertically | Row 1 Col 3   |
| Row 2 Col 1   | ::::           | Row 2 Col 3   |
| Row 3 Col 1   | ::::           | Row 2 Col 3   |

```

You can align the table contents, too. Just add at least two whitespaces at the opposite end of your text: Add two spaces on the left to align right, two spaces on the right to align left and two spaces at least at both ends for centered text.

Table with alignment		
right	center	left
left	right	center

Table with alignment		
XXXXXXXXXXXXX	XXXXXXXXXXXXX	XXXXXXXXXXXXX

This is how it looks in the source:

```
^           Table with alignment           ^^^
|           right|           center   |left   |
|left       |           right|           center   |
|XXXXXXXXXXXXX|XXXXXXXXXXXXX|XXXXXXXXXXXXX|
```

Note: Vertical alignment is not supported.

No Formatting

If you need to display text exactly like it is typed (without any formatting), enclose the area either with `<nowiki>` tags or even simpler, with double percent signs `%%`.

This is some text which contains addresses like this: `http://www.splitbrain.org` and `**formatting**`, but nothing is done with it. The same is true for `//__this__ text//` with a smiley ;-).

```
<nowiki>
This is some text which contains addresses like this:
http://www.splitbrain.org and **formatting**, but nothing is done with it.
</nowiki>
The same is true for %%//__this__ text// with a smiley ;-)%%.
```

Code Blocks

You can include code blocks into your documents by either indenting them by at least two spaces (like used for the previous examples) or by using the tags `<code>` or `<file>`.

```
This is text is indented by two spaces.
```

```
This is preformatted code all spaces are preserved: like           <-this
```

```
This is pretty much the same, but you could use it to show that you quoted a
file.
```

Those blocks were created by this source:

```
This is text is indented by two spaces.
```

```
<code>
This is preformatted code all spaces are preserved: like      <-this
</code>
```

```
<file>
This is pretty much the same, but you could use it to show that you quoted a
file.
</file>
```

Syntax Highlighting

[DokuWiki](#) can highlight sourcecode, which makes it easier to read. It uses the [GeSHi](#) Generic Syntax Highlighter - so any language supported by GeSHi is supported. The syntax uses the same code and file blocks described in the previous section, but this time the name of the language syntax to be highlighted is included inside the tag, e.g. `<code java>` or `<file java>`.

```
/**
 * The HelloWorldApp class implements an application that
 * simply displays "Hello World!" to the standard output.
 */
class HelloWorldApp {
    public static void main(String[] args) {
        System.out.println("Hello World!"); //Display the string.
    }
}
```

The following language strings are currently recognized: *4cs 6502acme 6502kickass 6502tasm 68000devpac abap actionscript3 actionscript ada aimms algol68 apache applescript apt_sources arm asm asp asymptote autoconf autohotkey autoit avisynth awk bascomavr bash basic4gl batch bf biblatex bibtex blitzbasic bnf boo caddcl cadlisp ceylon cfdg cfm chaiscript chapel cil c_loadrunner clojure c_mac cmake cobol coffeescript c cpp cpp-qt cpp-winapi csharp css cuesheet c_winapi dart dcl dcpu16 dcs delphi diff div dos dot d ecmascript eiffel email epc e erlang euphoria ezt f1 falcon fo fortran freebasic freeswitch fsharp gambas gdb genero genie gettext glsl gml gnuplot go groovy gwbasic haskell haxe hicest hq9plus html html4strict html5 icon idl ini inno intercal io ispfpanel java5 java javascript jcl j jquery julia kixtart klonec klonecpp kotlin latex lb ldif lisp llvm locobasic logtalk lolcode lotusformulas lotusscript lscript lsl2 lua m68k magiksf make mapbasic mathematica matlab mercury metapost mirc mk-61 mmix modula2 modula3 mpasm mxml mysql nagios netrexx newlisp nginx nimrod nsis oberon2 objc object ocaml-brief ocaml octave oobas oorexx oracle11 oracle8 oxygene oz parasail parigp pascal pcre perl6 perl per pf phix php-brief php pic16 pike pixelbender pli plsqli postgresql postscript povray powerbuilder powershell proftpd progress prolog properties providex purebasic pycon pys60 python qbasic qml q racket rails rbs rebol reg rexx robots roff rpmspec rsplus ruby rust sas sass scala scheme scilab scl sdlbasic smalltalk smarty spark sparql sql sshconfig standardml stonesscript swift systemverilog tcl tcl tcl tcl teraterm texgraph text thinbasic tsqli twig typoscript unicon upc urbi uscript vala vbnet vb vbscript vedit verilog vhdl vim visualfoxpro visualprolog whitespace whois winbatch wolfram xbasic xml xoyo xorg_conf xpp yaml z80 zxbasic*

There are additional [advanced options](#) available for syntax highlighting, such as highlighting lines or adding line numbers.

Downloadable Code Blocks

When you use the `<code>` or `<file>` syntax as above, you might want to make the shown code available for download as well. You can do this by specifying a file name after language code like this:

```
<file php myexample.php>
<?php echo "hello world!"; ?>
```

`</code>`

```
<?php echo "hello world!"; ?>
```

If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language code: `<code - myfile.foo>`.

Embedding HTML and PHP

You can embed raw HTML or PHP code into your documents by using the `<html>` or `<php>` tags. (Use uppercase tags if you need to enclose block level elements.)

HTML example:

```
<html>
This is some <span style="color:red;font-size:150%;">inline HTML</span>
</html>
<HTML>
<p style="border:2px dashed red;">And this is some block HTML</p>
</HTML>
```

```
<html> This is some inline HTML </html> <HTML> <p style="border:2px dashed red;">And this is
some block HTML</p> </HTML>
```

PHP example:

```
<php>
echo 'The PHP version: ';
echo phpversion();
echo ' (generated inline HTML)';
</php>
<PHP>
echo '<table class="inline"><tr><td>The same, but inside a block level
element:</td>';
```


```
echo '<td>'.phpversion().'</td>';
echo '</tr></table>';
</PHP>
```

```
<php> echo 'The PHP version: '; echo phpversion(); echo ' (inline HTML)'; </php> <PHP> echo
'<table class="inline"><tr><td>The same, but inside a block level element:</td>'; echo
'<td>'.phpversion().'</td>'; echo '</tr></table>'; </PHP>
```

Please Note: HTML and PHP embedding is disabled by default in the configuration. If disabled, the code is displayed instead of executed.

RSS/ATOM Feed Aggregation

[DokuWiki](#) can integrate data from external XML feeds. For parsing the XML feeds, [SimplePie](#) is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters:

Parameter	Description
any number	will be used as maximum number items to show, defaults to 8
reverse	display the last items in the feed first
author	show item authors names
date	show item dates
description	show the item description. If  HTML is disabled all tags will be stripped
nosort	do not sort the items in the feed
n[dhm]	refresh period, where d=days, h=hours, m=minutes. (e.g. 12h = 12 hours).

The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. [DokuWiki](#) will generally try to supply a cached version of a page, obviously this is inappropriate when the page contains dynamic external content. The parameter tells [DokuWiki](#) to re-render the page if it is more than *refresh period* since the page was last rendered.

By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the reverse parameter, or display the feed as is with nosort.

Example:

```
{ {rss>http://slashdot.org/index.rss 5 author date 1h } }
```


- [Commodore's Callback 8020 Is a \\$499 Flip Phone That Blocks Social Media and Browsers](#) by BeauHD (2026/06/17 08:00)
- [Binance Set To Lose Permission To Operate In EU](#) by BeauHD (2026/06/17 07:00)
- [France To Stop Certifying Products Without Quantum-Safe Encryption](#) by BeauHD (2026/06/17 06:00)
- [Mobileye Is Entering the US Robotaxi Market With Standalone Service](#) by BeauHD (2026/06/17 05:00)
- [Snap's First Consumer AI Glasses Are Coming This Fall For \\$2,195](#) by BeauHD (2026/06/17 04:00)

Control Macros

Some syntax influences how DokuWiki renders a page without creating any output it self. The following control macros are available:

Macro	Description
~~NOTOC~~	If this macro is found on the page, no table of contents will be created
~~NOCACHE~~	DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call

Syntax Plugins

DokuWiki's syntax can be extended by  [Plugins](#). How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular DokuWiki installation:

- [Add New Page plugin 2025-09-21](#) by [Damien Regad](#), [Benjamin Santalucia](#), [Sam Wilson](#) and [other contributors](#)
Adds a "new page form" to any wiki page.
- [Bootstrap Wrapper Plugin 2022-09-22](#) by [Giuseppe Di Terlizzi](#)
Bootstrap Wrapper for DokuWiki
- [catlist plugin 2023-12-16](#) by [Félix Faisant](#)
List pages and namespaces recursively
- [Changes Plugin 2023-12-14](#) by [Andreas Gohr](#)
List the most recent changes of the wiki
- [Command Line Interface \(CLI\) Plugin 2020-08-18](#) by [Schplurtz le Déboulonné](#)
Renders transcripts of command line interactions, e.g. for shell and dynamic language interpreter tutorials
- [Comment Syntax support 2022-01-01](#) by [Satoshi Sahara](#)
Allow to use source comment syntax to leave edit instructions of the page. Comments are visible only in the source view, not rendered as any page elements.
- [Countdown Plugin 2020-11-01](#) by [Ron Peters](#), [Ekkart Kleinod](#), [Luis Machuca Bezzaza](#)
Countdown to a specific date
- [cssperpage 2018-09-15](#) by [Myron Turner](#)
enables per page styling
- [DataTables Plugin 2023-08-31](#) by [Giuseppe Di Terlizzi](#)
Add DataTables support to DokuWiki
- [Calendar PlugIn with CalDAV sharing support 2025-07-10](#) by [Andreas Boehler](#), [Scott Lee Chua](#)
Create one calendar per page and share/subscribe via CalDAV
- [daycalc plugin 2025-06-16](#) by [Alexandra Levine](#)
Calculate the number of days between a start date and an end date.
- [Diagrams plugin 2025-10-15](#) by [Innovakom + CosmoCode](#)
Embed diagrams.net editor (formerly draw.io)
- [Diagram plugin 2021-02-21](#) by [Nikita Melnichenko](#)
Constructs diagrams
- [Prism Highlighter 2023-11-25](#) by [Adam Mnemonic](#)

- Syntax highlighting of source code snippets in DokuWiki page using PRISM engine
- [do plugin](#) 2024-05-12 by [Andreas Gohr](#)
Assign tasks within the wiki
 - [Dw2Pdf plugin](#) 2026-01-08 by [Andreas Gohr](#) and [Luigi Micco](#)
DokuWiki to PDF converter
 - [Gallery Plugin](#) 2024-04-30 by [Andreas Gohr](#)
Creates a gallery of images from a namespace or RSS/ATOM feed
 - [iframe plugin](#) 2023-08-17 by [Christopher Smith](#)
Allows external URLs to be loaded into an iframe in your DokuWiki page.
 - [include plugin](#) 2025-07-22 by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael Klier](#), [Esther Brunner](#)
Functions to include another page in a wiki page
 - [Info Plugin](#) 2020-06-04 by [Andreas Gohr](#)
Displays information about various DokuWiki internals
 - [MathJax plugin](#) 2021-11-20 by [Mark Liffiton](#)
Enables MathJax (<https://www.mathjax.org/>) parsing of TeX math expressions in wiki pages
 - [MediaList Plugin](#) 2016-08-24 by [Satoshi Sahara](#)
show a list of media files referred in a given page or stored in a given namespace.
 - [OpenAs Plugin](#) 2022-02-14 by [Myron Turner](#)
File utility for renaming and saving-as, and creating new pages from templates
 - [Outliner Plugin](#) 2024-01-23 by [Vincent Voisin](#)
Allows collapsible outline layout
 - [Pagelist Plugin](#) 2023-08-27 by [Matthias Schulte](#), [Michael Hamann](#), [Michael Klier](#), [Gina Haeussge](#)
Lists pages in a nice formatted way
 - [PDF.js](#) 2020-06-29 by [Szymon Olewniczak](#)
Show pdf files using PDF.js
 - [Search Form Plugin](#) 2024-02-08 by [Gerrit Uitslag](#), (previous: [Adolfo González Blázquez](#))
Inserts a search form in any page
 - [Snippets Plugin](#) 2022-10-07 by [Myron Turner](#)
Provides toolbar button+popup for template insertion; can track and insert snippet updates
 - by
 - [SyntaxHighlighter4 Plugin](#) 2020-05-13 by [CrazyMax](#)
Alternative to GeSHi server-side code highlighting with client-side SyntaxHighlighter 4 by Alex Gorbachev
 - [Tag Plugin](#) 2023-10-17 by [Michael Hamann](#), [Gina Häussge](#), [Christopher Smith](#), [Michael Klier](#), [Esther Brunner](#)
tag wiki pages
 - [ToDo](#) 2025-08-26 by [Leo Eibler](#), [Christian Marg](#), [Markus Gschwendt](#), [Robert Weinmeister](#)
Create a checkbox based todo list with optional user assignment (basic syntax: `<todo>This is a ToDo</todo>`). It can also be used as a lightweight task list management system.
 - [Translation Plugin](#) 2025-05-20 by [Andreas Gohr](#)
Supports the easy setup of a multi-language wiki.
 - [Typography plugin](#) 2020-07-31 by [Satoshi Sahara](#)
Enable typesetting capabilities with CSS font properties such as font face, size, weight, and color of text
 - [Video Sharing Site Plugin](#) 2025-12-10 by [Andreas Gohr](#)
Easily embed videos from various Video Sharing sites. Example: `{{youtube>XXXXXX}}`
 - [Wrap Plugin](#) 2023-08-13 by [Anika Henke](#)
Universal plugin which combines functionalities of many other plugins. Wrap wiki text inside containers (divs or spans) and give them a class (choose from a variety of preset classes), a width and/or a language with its associated text direction.

1)

This is a footnote

2)

when the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing

From:

<http://theta5912.net/> - reth

Permanent link:

http://theta5912.net/doku.php?id=public:others:elements_of_document&rev=1658837993

Last update: **2022/07/26 21:19**

